

ROVELO

INSTINCT SUV

PERFORMANCE RATINGS:



T, H, V, W SPEED RATINGS

CLASIFICACIONES DE VELOCIDAD T, H, V, W



The SUV/UV has become the vehicle of choice in North America thanks to their ability to carry passengers and cargo for a go-anywhere, do-anything attitude. The Rovelo Instinct SUV tire was engineered to complement the SUV segment providing excellent handling and traction along with the heavier loads of SUVs. The wide tread surface and unique shoulder profile delivers increased contact with the road for better handling. Our proprietary rubber compound enhances ride comfort, while reducing road vibration and road noise. Tread design and rubber compounds were specially engineered to provide outstanding traction on wet and dry roads, while also shortening braking distance. Combined with a 60,000 mile tread life warranty, the Rovelo Instinct SUV offers unmatched performance and reliability. Short commute or destination drive, the Instinct SUV can be trusted for a quiet, comfortable ride every time.

HANDLING

Wide tread surface plus a unique shoulder profile design delivers more even contact pressure increasing handling performance.

COMFORT

Proprietary rubber under tread compound enhances ride comfort, while reducing road vibration and road noise.

TRACTION

4 wide circumferential grooves work with lateral grooves that effectively channel away moisture. This ensures effective grounding and enhances wet braking and handling performance.



El vehículo utilitario deportivo (SUV)/UV se ha vuelto el vehículo de elección en Norteamérica gracias a su habilidad para transportar pasajeros y cargamento a ir a cualquier parte, con actitud de hacer cualquier cosa. El neumático Rovelo Instinct SUV fue diseñado para complementar al segmento de los SUV, proporcionándoles excelentes manejo y tracción junto con las cargas más pesadas de los SUV. Nuestro compuesto patentado de caucho mejora la comodidad de la conducción, mientras reduce la vibración y el ruido del camino. El diseño de la banda de rodamiento y los compuestos de caucho fueron creados especialmente para proporcionar tracción sobresaliente en caminos húmedos y secos, mientras que también acortan la distancia de frenado. Combinado con la garantía de vida útil de banda de rodamiento de 60,000 millas, el Rovelo Instinct SUV ofrece desempeño y confiabilidad inigualables. Transporte corto o conducción hasta un destino, puede confiar en el Instinct SUV para una conducción silenciosa y cómoda cada vez.

MANEJO

La superficie de banda de rodamiento amplia más un diseño de perfil único de hombro proporcionan presión de contacto más uniforme, incrementando el desempeño de manejo.

COMODIDAD

El compuesto patentado de caucho bajo la banda de rodamiento mejora la comodidad de la conducción, mientras reduce la vibración y el ruido del camino.

TRACCIÓN

Cuatro surcos circumferenciales amplios trabajan con los surcos laterales que canalizan efectivamente la humedad para alejarla del neumático. Esto asegura un contacto efectivo con el suelo, y mejora el frenado húmedo y el desempeño de manejo.



INSTINCT SUV

Part #	Size	LI/SR	TD	OD	SW	RW	UTQG	MAX LOAD (1X)
				32/in.	in.	in.		
4120098V	215/65R16	98H	10	27.0	8.7	6.5	700 A A	1653@44
4120096V	215/70R16	100H	10	27.9	8.7	6.5	700 A A	1764@44
4120099V	235/60R16	100H	10	27.1	9.4	7.0	700 A A	1764@44
4120118V	245/70R16	107T	10	29.5	9.8	7.0	700 A A	2149@44
4120106V	255/70R16	111H	10	30.1	10.2	7.5	700 A A	2403@44
4120105V	265/70R16	112H	10	30.6	10.7	8.0	700 A A	2469@44
4120100V	215/60R17	96H	10	27.2	8.7	6.5	700 A A	1565@44
4120120V	225/55R17	97V	10	26.8	9.2	7.0	700 A A	1609@44
4120108V	225/60R17	99H	10	27.6	9	6.5	700 A A	1709@44
4120109V	225/65R17	102H	10	28.5	9	6.5	700 A A	1874@44
4120128V	235/55R17	99V	10	27.2	9.6	7.5	700 A A	1709@44
4120097V	235/60R17	102H	10	28.1	9.4	7.0	700 A A	1874@44
4120107V	235/65R17	104H	10	29.1	9.4	7.0	700 A A	1984@44
4120117V	245/65R17	107H	10	29.5	9.8	7.0	700 A A	2149@44
4120115V	255/60R17	106H	10	29.1	10.2	7.5	700 A A	2094@44
4120094V	265/65R17	112H	10	30.6	10.7	8.0	700 A A	2469@44
4120104V	215/55R18	95H	10	27.3	8.9	7.0	700 A A	1521@44
4120091V	225/55R18	98V	10	27.8	9.2	7.0	700 A A	1653@44
4120114V	225/60R18	100H	10	28.6	9	6.5	700 A A	1764@44
4120119V	235/50R18	97V	10	27.3	9.6	7.5	700 A A	1609@44
4120089V	235/55R18	100V	10	28.1	9.6	7.5	700 A A	1764@44
4120116V	235/60R18	107V XL	10	29.1	9.4	7.0	700 A A	2149@50
4120085V	235/65R18	106H	10	30	9.4	7.0	700 A A	2094@44
4120113V	245/60R18	105H	10	29.6	9.8	7.0	700 A A	2039@44
4120127V	255/55R18	109V XL	10	29	10.4	8.0	700 A A	2271@50
4120090V	255/65R18	111T	10	31.1	10.2	7.5	700 A A	2403@44
4120112V	265/60R18	110H	10	30.5	10.7	8.0	700 A A	2337@44
4120121V	225/55R19	99V	10	28.8	9.2	7.0	700 A A	1709@44
4120095V	235/45R19	95V	10	27.4	9.3	8.0	700 A A	1521@44
4120092V	235/50R19	103V XL	10	28.3	9.6	7.5	700 A A	1929@50
4120132V	235/55R19	105V XL	10	29.2	9.6	7.5	700 A A	2039@50
4120129V	245/55R19	103V	10	29.6	10	7.5	700 A A	1929@44
4120088V	255/50R19	107V XL	10	29.1	10.4	8.0	700 A A	2149@50
4120123V	255/55R19	111V XL	10	30	10.4	8.0	700 A A	2403@50
4120111V	255/60R19	109H	10	31.1	10.2	7.5	700 A A	2271@44
4120086V	265/50R19	110V XL	10	29.5	10.9	8.5	700 A A	2337@50
4120130V	235/55R20	105V XL	10	30.2	9.6	7.5	700 A A	2039@50
4120133V	245/50R20	102V	10	29.7	10	7.5	700 A A	1874@44
4120110V	245/60R20	107H	10	31.6	9.8	7.0	700 A A	2149@44
4120084V	255/50R20	109V XL	10	30.1	10.4	8.0	700 A A	2271@50
4120125V	255/55R20	110V XL	10	31	10.4	8.0	700 A A	2337@50
4120122V	265/50R20	107H	10	30.5	10.9	8.5	700 A A	2149@44
4120124V	275/40R20	106W XL	10	28.7	10.9	9.5	700 A A	2094@50
4120101V	265/40R21	105W XL	10	29.3	10.7	9.5	700 A A	2039@50
4120102V	275/40R21	107W XL	10	29.6	10.9	9.5	700 A A	2149@50
4120131V	275/45R21	110W XL	10	30.7	10.7	9.0	700 A A	2337@50
4120126V	285/40R21	109W XL	10	30	11.4	10.0	700 A A	2271@50
4120103V	295/35R21	107W XL	10	29.1	11.9	10.5	700 A A	2149@50
4120093V	315/40R21	115W XL	10	30.9	12.6	11.0	700 A A	2679@50