

ROVELO RIDGETRAK A/T II

LIGHT TRUCK



The Ridgetrak A/T II is an updated all-terrain tire for pickup trucks and SUVs. Enhanced 3PMS certified traction, deep tread depth while incorporating a wide tread face provides superior performance for all on and off road driving conditions. Known for consistent reliability, the Ridgetrak A/T II is engineered to be your trusted all-terrain tire providing a quiet comfortable driving experience.

COMFORT: Finite Element Analysis simulation software optimizes pitch sequence to reduce resonance effects and aids in a quiet vehicle cabin.

ENHANCED TRACTION:

3PMS Certified, deep all-terrain tread lugs and altered shoulder tread blocks work together providing trusted traction on all terrains and in all seasons.

TREADWEAR: A Wide tread footprint with additional shoulder support promotes even pressure distribution and avoids irregular wear.

El Ridgetrak A/T II es un neumático todoterreno actualizado para camionetas pickup y SUV. Tracción certificada 3PMS y profundidad de la banda de rodadura mejoradas, y la incorporación de una superficie de la banda de rodadura amplia proporciona desempeño superior para todas las condiciones de conducción dentro y fuera del camino. Conocidos por su confiabilidad constante, el Ridgetrak A/T está diseñado para ser su neumático todoterreno de confianza, que proporciona una experiencia de conducción cómoda y silenciosa.

COMODIDAD: El software de simulación de elemento finito optimiza la secuencia de paso para reducir los efectos de resonancia y ayuda a tener una cabina de vehículo silenciosa.

TRACCIÓN MEJORADA: Los gajos profundos de la banda de rodadura todoterreno y los bloques de la banda de rodadura del hombro, con certificación 3PMS, trabajan en conjunto para proporcionar tracción confiable en todos los terrenos y en todas las temporadas.

DESGASTE DE LA BANDA DE RODAMIENTO: La huella amplia de la banda de rodadura con apoyo de hombro adicional promueve distribución de presión más uniforme y evita el desgaste irregular.



Part #	Size	Ply	LI/SR	TD	OD	SW	RW	UTQG	MAX LOAD (1X)	MAX LOAD (2X)
					32/in.	in.	in.			
4120258V	235/75R15	XL	109S	13	28.9	9.25	6	620/A/B	2271@50	-
4120259V	235/70R16	-	106S	13	29.0	9.45	7	620/A/B	2094@44	-
4120260V	245/75R16	-	111S	13	30.5	9.76	7	620/A/B	2403@44	-
4120261V	265/70R16	-	112T	13	30.6	10.71	8	620/A/B	2469@44	-
4120508V	265/75R16	-	116S	13	31.7	10.51	7	620/A/B	2756@44	-
4120509V	235/65R17	-	104S	13	29.1	9.45	7	620/A/B	1984@44	-
4120510V	245/65R17	-	107S	13	29.5	9.76	7	620/A/B	2149@44	-
4120511V	245/70R17	-	110T	13	30.6	9.76	7	620/A/B	2337@44	-
4120512V	255/65R17	-	110T	13	30.1	10.24	7	620/A/B	2337@44	-
4120513V	265/65R17	-	112S	13	30.6	10.71	8	620/A/B	2469@44	-
4120514V	265/70R17	-	115S	13	31.7	10.71	8	620/A/B	2679@44	-
4120515V	265/65R18	-	114T	13	31.5	10.71	8	620/A/B	2601@44	-
4120516V	265/70R18	-	116T	13	32.6	10.71	8	620/A/B	2756@44	-
4120517V	275/65R18	-	116T	13	32.1	10.98	8	620/A/B	2756@44	-
4120518V	265/50R20	XL	111T	13	30.5	10.91	8	620/A/B	2403@50	-
4120519V	275/60R20	-	115T	13	33.0	10.98	8	620/A/B	2679@44	-
4120526V	285/45R22	XL	114H	13	32.1	11.22	9	620/A/B	2601@49	-
4120533V	LT225/75R16	10PR	115/112S	16	29.3	8.78	6	-	2680@80	2470@80
4120534V	LT235/85R16	10PR	120/116S	16	31.7	9.25	6	-	3042@80	2778@80
4120535V	LT245/75R16	10PR	120/116S	16	30.5	9.76	7	-	3042@80	2778@80
4120536V	LT265/75R16	10PR	123/120S	16	31.7	10.51	7	-	3415@80	3085@80
4120537V	LT235/80R17	10PR	120/117R	16	31.8	9.25	6	-	3085@80	2835@80
4120538V	LT245/70R17	10PR	119/116S	16	30.6	9.76	7	-	3000@80	2755@80
4120539V	LT245/75R17	10PR	121/118S	16	31.5	9.76	7	-	3195@80	2910@80
4120540V	LT265/70R17	10PR	121/118S	16	31.7	10.71	8	-	3415@80	3085@80
4120541V	LT285/70R17	10PR	121/118S	16	32.8	11.50	8	-	3750@80	3415@80
4120542V	LT315/70R17	10PR	121/118S	16	34.4	12.72	9	-	3750@80	3415@80
4120543V	LT265/70R18	10PR	124/121S	16	32.6	10.71	8	-	3525@80	3195@80
4120544V	LT275/65R18	10PR	123/120R	16	32.1	10.98	8	-	3415@80	3085@80
4120545V	LT275/70R18	10PR	125/122R	16	33.2	10.98	8	-	3640@80	3305@80
4120546V	LT265/60R20	10PR	121/118R	16	32.5	10.71	8	-	3195@80	2910@80
4120547V	LT275/55R20	10PR	120/117R	16	31.9	11.18	8	-	3085@80	2835@80
4120548V	LT275/60R20	10PR	123/120R	16	33.0	10.98	8	-	3415@80	3085@80
4120549V	LT275/65R20	10PR	126/123R	16	34.1	10.98	8	-	3750@80	3415@80
4120550V	LT285/60R20	10PR	125/122R	16	33.5	11.50	8	-	3640@80	3305@80
4120551V	LT305/55R20	10PR	121/118R	16	33.2	12.44	9	-	3195@65	2910@65
4120527V	31x10.50R15LT	6PR	109S	16	30.5	10.55	8	-	2270@50	-
4120529V	33x12.50R18LT	10PR	118S	16	32.5	12.52	10	-	2910@65	-
4120531V	33x12.50R20LT	10PR	114S	16	32.5	12.52	10	-	2600@65	-
4120528V	35x12.50R17LT	10PR	125R	16	34.5	12.52	10	-	3640@80	-
4120530V	35x12.50R18LT	10PR	123R	16	34.5	12.52	10	-	3415@65	-
4120532V	35x12.50R20LT	10PR	121R	16	34.5	12.52	10	-	3195@65	-