

ROVELO



PASSENGER & LIGHT TRUCK
ROVELOTIREUSA.COM

A blurred highway with power lines and a green tire tread graphic at the bottom.

ROVELO

TABLE OF CONTENTS

PASSENGER & LIGHT TRUCK TIRE 2023



4 **INSTINCT AS01**
ALL SEASON TIRE



6 **INSTINCT SUV**
ALL SEASON SUV TIRE



8 **RIDGETRAK H/T HT02**
HWY TERRAIN TIRE



10 **RIDGETRAK A/T II**
ALL TERRAIN TIRE



12 **RIDGETRAK R/T RT01**
RUGGED TERRAIN LIGHT TRUCK

ROVELO

INSTINCT AS01

ALL SEASON TIRE

PERFORMANCE RATINGS:

Wet Performance:  8

Dry Performance:  8

Ride Comfort:  9

Quietness:  9

Tread Life:  9

T,H,V,W SPEED RATINGS
60,000 MILE TREADLIFE WARRANTY

CLASIFICACIONES DE VELOCIDAD T, H, V, W
GARANTÍA DE LA BANDA DE RODAMIENTO DE
60,000 MILLAS



ALL SEASON TOURING

The Rovelo Instinct AS01 all-season touring tire lets you and your vehicle become one with the road. Four wide circumferential tire grooves help channel water away from the tire to provide excellent wet and dry traction. The center rib provides directional stability with biting edges for added traction and the wide shoulder lugs promote even wear and fantastic cornering. The balanced variable pitch design gives you a quiet, comfortable ride while the 60,000 mile tread life warranty will put your mind at ease knowing this tire was built to last. Comfort, handling, and traction are engineered to come natural to the Rovelo INSTINCT AS01.

CENTER RIB WITH ANGLED SIPES

Provides confident stability with enhanced traction

BALANCED VARIABLE PITCH SHOULDER DESIGN

Promotes quiet and comfortable ride

FULL SIPED INNER TREAD BLOCKS

Efficient water evacuation design promotes enhanced wet performance

TOURING PARA TODAS LAS TEMPORADAS

El neumático touring para todas las temporadas Rovelo Instinct AS01 le permite a usted y a su vehículo convertirse en uno con el camino. Cuatro surcos de neumático circunferenciales amplios ayudan a canalizar el agua para alejarla del neumático y proporcionar tracción húmeda y seca excelente. La costilla central proporciona estabilidad direccional con bordes marcados para tracción agregada, y los huecos de los hombros promueven el desgaste uniforme y un fantástico giro. El diseño de paso variable balanceado le proporciona una conducción silenciosa y cómoda mientras que la garantía de vida útil de la banda de rodamiento de 60,000 millas le dará la tranquilidad de saber que este neumático está fabricado para durar. Comodidad, manejo y tracción están diseñados para ser parte natural de el Rovelo INSTINCT AS01.

COSTILLA CENTRAL CON MICROSURCOS EN ÁNGULO:

Proporciona estabilidad confiable con tracción mejorada

DISEÑO DE HOMBRO CON PASO VARIABLE BALANCEADO:

Promueve una conducción silenciosa y cómoda

BLOQUES DE BANDA DE RODAMIENTO INTERNO CON MICROSURCOS COMPLETOS:

El diseño para evacuación eficiente de agua promueve un desempeño húmedo mejorado



INSTINCT AS01

ALL SEASON TOURING / TOURING PARA TODAS LAS TEMPORADAS


Part #	Size	LI/SR	TD	OD	SW	RW	UTQG	MAX LOAD (1X)
				32/in.	in.	in.		
9630963	175/65R14	86T XL	10	23.0	7.0	5.0	420 A A	1168@50
9630958	175/70R14	84T	10	23.7	7.0	5.0	420 A A	1102@44
9630947	185/65R14	86H	10	23.5	7.4	5.5	420 A A	1168@44
9630955	195/70R14	91T	10	24.8	7.9	6.0	420 A A	1356@44
9630978	175/55R15	77H	10	22.6	7.2	5.5	420 A A	908@44
9630971	175/65R15	84H	10	24.0	7.0	5.0	420 A A	1102@44
9630957	185/55R15	82V	10	23.0	7.6	6.0	420 A A	1047@44
9630945	185/60R15	88H XL	10	23.7	7.4	5.5	420 A A	1235@50
9630939	185/65R15	92H XL	10	24.4	7.4	5.5	420 A A	1389@50
9630941	195/60R15	88H	10	24.2	7.9	6.0	420 A A	1235@44
9630932	195/65R15	91H	10	25.0	7.9	6.0	420 A A	1356@44
9630964	205/60R15	95H XL	10	24.7	8.2	6.0	420 A A	1521@50
9630942	205/65R15	94H	10	25.5	8.2	6.0	420 A A	1477@44
9630953	205/70R15	96T	10	26.3	8.2	6.0	420 A A	1565@44
9630946	215/70R15	98T	10	26.9	8.7	6.5	420 A A	1653@44
9630972	195/50R16	84V	10	23.7	7.9	6.0	420 A A	1102@44
9630970	195/55R16	87H	10	24.4	7.9	6.0	420 A A	1201@44
9630966	205/50R16	87H	10	24.1	8.4	6.5	420 A A	1201@44
9630929	205/55R16	91H	10	24.9	8.4	6.5	420 A A	1356@44
9630938	205/60R16	92H	10	25.7	8.2	6.0	420 A A	1389@44
9630937	205/65R16	95H	10	26.5	8.2	6.0	420 A A	1521@44
9630940	215/55R16	97H XL	10	25.3	8.9	7.0	420 A A	1609@50
9630931	215/60R16	95H	10	26.1	8.7	6.5	420 A A	1521@44
9630944	215/65R16	98T	10	27.0	8.7	6.5	420 A A	1653@44
9630935	225/60R16	98H	10	26.6	9.0	6.5	420 A A	1653@44
9630954	225/65R16	100H	10	27.5	9.0	6.5	420 A A	1764@44
9630977	235/60R16	100V	10	27.1	9.4	7.0	420 A A	1764@44
9630965	235/65R16	103T	10	28.0	9.4	7.0	420 A A	1929@44
9630959	205/50R17	89V	10	25.1	8.4	6.5	420 A A	1728@44
9630967	215/45R17	87W	10	24.6	8.4	7.0	420 A A	1201@44
9630960	215/50R17	91V	10	25.5	8.9	7.0	420 A A	1356@44
9630930	215/55R17	94V	10	26.3	8.9	7.0	420 A A	1477@44
9630950	215/60R17	96T	10	27.2	8.7	6.5	420 A A	1565@44
9630952	215/65R17	99T	10	28.0	8.7	6.5	420 A A	1709@44
9630949	225/45R17	91V	10	25.0	8.9	7.5	420 A A	1356@44
9630934	225/50R17	94V	10	25.9	9.2	7.0	420 A A	1477@44
9630936	225/55R17	97V	10	26.8	9.2	7.0	420 A A	1609@44
9630943	225/60R17	99H	10	27.6	9.0	6.5	420 A A	1709@44
9630933	225/65R17	102T	10	28.5	9.0	6.5	420 A A	1874@44
9630969	235/45R17	97W XL	10	25.4	9.3	8.0	420 A A	1609@50
9630962	235/55R17	99V	10	27.2	9.6	7.5	420 A A	1709@44
9630976	225/40R18	92W XL	10	25.1	9.1	8.0	420 A A	1389@50
9630961	225/50R18	95H	10	26.9	9.2	7.0	420 A A	1521@44
9630968	235/45R18	94V	10	26.3	9.3	8.0	420 A A	1477@44
9630956	235/50R18	97V	10	27.3	9.6	7.5	420 A A	1609@44
9630948	235/55R18	100V	10	28.1	9.6	7.5	420 A A	1764@44
9630951	235/60R18	103H	10	29.1	9.4	7.0	420 A A	1929@44
9630975	245/40R18	97W XL	10	25.7	9.8	8.5	420 A A	1609@50
9630974	245/45R18	100W XL	10	26.7	9.6	8.0	420 A A	1764@50
9630973	235/55R19	105V XL	10	29.2	9.6	7.5	420 A A	2039@50

ROVELO

INSTINCT SUV

ALL SEASON SUV TIRE

PERFORMANCE RATINGS:



T,H,V,W SPEED RATINGS

CLASIFICACIONES DE VELOCIDAD T, H, V, W



The SUV/CUV has become the vehicle of choice in North America thanks to their ability to carry passengers and cargo for a go-anywhere, do-anything attitude. The Rovelo Instinct SUV tire was engineered to compliment the SUV segment providing excellent handling and traction along with the heavier loads of SUVs. The wide tread surface and unique shoulder profile delivers increased contact with the road for better handling. Our proprietary rubber compound enhances ride comfort, while reducing road vibration and road noise. Tread design and rubber compounds were specially engineered to provide outstanding traction on wet and dry roads, while also shortening braking distance. Combined with a 60,000 mile tread life warranty, the Rovelo Instinct SUV offers unmatched performance and reliability. Short commute or destination drive, the Instinct SUV can be trusted for a quiet, comfortable ride every time.

HANDLING

Wide tread surface plus a unique shoulder profile design delivers more even contact pressure increasing handling performance.

COMFORT

Proprietary rubber under tread compound enhances ride comfort, while reducing road vibration and road noise.

TRACTION

4 wide circumferential grooves work with lateral grooves that effectively channel away moisture. This ensures effective grounding and enhances wet braking and handling performance.

El vehículo utilitario deportivo (SUV)/VUC se ha vuelto el vehículo de elección en Norteamérica gracias a su habilidad para transportar pasajeros y cargamento a ir a cualquier parte, con actitud de hacer cualquier cosa. El neumático Rovelo Instinct SUV fue diseñado para complementar al segmento de los SUV, proporcionándoles excelentes manejo y tracción junto con las cargas más pesadas de los SUV. Nuestro compuesto patentado de caucho mejora la comodidad de la conducción, mientras reduce la vibración y el ruido del camino. El diseño de la banda de rodadura y los compuestos de caucho fueron creados especialmente para proporcionar tracción sobresaliente en caminos húmedos y secos, mientras que también acortan la distancia de frenado. Combinado con la garantía de vida útil de banda de rodadura de 60,000 millas, el Rovelo Instinct SUV ofrece desempeño y confiabilidad inigualables. Transporte corto o conducción hasta un destino, puede confiar en el Instinct SUV para una conducción silenciosa y cómoda cada vez.

MANEJO

La superficie de banda de rodadura amplia más un diseño de perfil único de hombro proporcionan presión de contacto más uniforme, incrementando el desempeño de manejo.

COMODIDAD

El compuesto patentado de caucho bajo la banda de rodadura mejora la comodidad de la conducción, mientras reduce la vibración y el ruido del camino.

TRACCIÓN

Cuatro surcos circunferenciales amplios trabajan con los surcos laterales que canalizan efectivamente la humedad para alejarla del neumático. Esto asegura un contacto efectivo con el suelo, y mejora el frenado húmedo y el desempeño de manejo.



INSTINCT SUV

ALL SEASON SUV TIRE


Part #	Size	LI/SR	TD	OD	SW	RW	UTQG	MAX LOAD (1X)
				32/in.	in.	in.		
4120098V	215/65R16	98H	10	27.0	8.7	6.5	700 A A	1653@44
4120096V	215/70R16	100H	10	27.9	8.7	6.5	700 A A	1764@44
4120099V	235/60R16	100H	10	27.1	9.4	7.0	700 A A	1764@44
4120118V	245/70R16	107T	10	29.5	9.8	7.0	700 A A	2149@44
4120106V	255/70R16	111H	10	30.1	10.2	7.5	700 A A	2403@44
4120105V	265/70R16	112H	10	30.6	10.7	8.0	700 A A	2469@44
4120100V	215/60R17	96H	10	27.2	8.7	6.5	700 A A	1565@44
4120120V	225/55R17	97V	10	26.8	9.2	7.0	700 A A	1609@44
4120108V	225/60R17	99H	10	27.6	9	6.5	700 A A	1709@44
4120109V	225/65R17	102H	10	28.5	9	6.5	700 A A	1874@44
4120128V	235/55R17	99V	10	27.2	9.6	7.5	700 A A	1709@44
4120097V	235/60R17	102H	10	28.1	9.4	7.0	700 A A	1874@44
4120107V	235/65R17	104H	10	29.1	9.4	7.0	700 A A	1984@44
4120117V	245/65R17	107H	10	29.5	9.8	7.0	700 A A	2149@44
4120115V	255/60R17	106H	10	29.1	10.2	7.5	700 A A	2094@44
4120094V	265/65R17	112H	10	30.6	10.7	8.0	700 A A	2469@44
4120104V	215/55R18	95H	10	27.3	8.9	7.0	700 A A	1521@44
4120091V	225/55R18	98V	10	27.8	9.2	7.0	700 A A	1653@44
4120114V	225/60R18	100H	10	28.6	9	6.5	700 A A	1764@44
4120119V	235/50R18	97V	10	27.3	9.6	7.5	700 A A	1609@44
4120089V	235/55R18	100V	10	28.1	9.6	7.5	700 A A	1764@44
4120116V	235/60R18	107V XL	10	29.1	9.4	7.0	700 A A	2149@50
4120085V	235/65R18	106H	10	30	9.4	7.0	700 A A	2094@44
4120113V	245/60R18	105H	10	29.6	9.8	7.0	700 A A	2039@44
4120127V	255/55R18	109V XL	10	29	10.4	8.0	700 A A	2271@50
4120090V	255/65R18	111T	10	31.1	10.2	7.5	700 A A	2403@44
4120112V	265/60R18	110H	10	30.5	10.7	8.0	700 A A	2337@44
4120121V	225/55R19	99V	10	28.8	9.2	7.0	700 A A	1709@44
4120095V	235/45R19	95V	10	27.4	9.3	8.0	700 A A	1521@44
4120092V	235/50R19	103V XL	10	28.3	9.6	7.5	700 A A	1929@50
4120132V	235/55R19	105V XL	10	29.2	9.6	7.5	700 A A	2039@50
4120129V	245/55R19	103V	10	29.6	10	7.5	700 A A	1929@44
4120088V	255/50R19	107V XL	10	29.1	10.4	8.0	700 A A	2149@50
4120123V	255/55R19	111V XL	10	30	10.4	8.0	700 A A	2403@50
4120111V	255/60R19	109H	10	31.1	10.2	7.5	700 A A	2271@44
4120086V	265/50R19	110V XL	10	29.5	10.9	8.5	700 A A	2337@50
4120130V	235/55R20	105V XL	10	30.2	9.6	7.5	700 A A	2039@50
4120133V	245/50R20	102V	10	29.7	10	7.5	700 A A	1874@44
4120110V	245/60R20	107H	10	31.6	9.8	7.0	700 A A	2149@44
4120084V	255/50R20	109V XL	10	30.1	10.4	8.0	700 A A	2271@50
4120125V	255/55R20	110V XL	10	31	10.4	8.0	700 A A	2337@50
4120122V	265/50R20	107H	10	30.5	10.9	8.5	700 A A	2149@44
4120124V	275/40R20	106W XL	10	28.7	10.9	9.5	700 A A	2094@50
4120101V	265/40R21	105W XL	10	29.3	10.7	9.5	700 A A	2039@50
4120102V	275/40R21	107W XL	10	29.6	10.9	9.5	700 A A	2149@50
4120131V	275/45R21	110W XL	10	30.7	10.7	9.0	700 A A	2337@50
4120126V	285/40R21	109W XL	10	30	11.4	10.0	700 A A	2271@50
4120103V	295/35R21	107W XL	10	29.1	11.9	10.5	700 A A	2149@50
4120093V	315/40R21	115W XL	10	30.9	12.6	11.0	700 A A	2679@50

ROVELO

RIDGETRAK H/T HT02

HWY TERRAIN TIRE

PERFORMANCE RATINGS:



H, S, R, T AND V SPEED RATINGS
UTQG 700 A A



HIGHWAY TERRAIN

The RIDGETRAK H/T HT02 is an excellent all-season highway terrain tire for light trucks, SUVs and crossovers, providing exceptional traction, a quiet ride, and consistent handling for a comfortable and enjoyable drive every time. The RIDGETRAK H/T HT02 is available in P-metric and LT.

EXCELLENT TRACTION

Special polymer compound with zig-zag siping design enhances wet traction with confident control for all weather and road conditions.

RIDE COMFORT

Modern noise simulation technology optimizes tread design for a quiet ride.

CONSISTENT HANDLING

Shoulder tie-bar design in the lateral grooves increase stability and promotes even wear.

TERRENO DE CARRETERA

El RIDGETRAK H/T HT02 es un excelente neumático de terreno de carretera para todas las temporadas para camionetas ligeras, SUV y crossovers, proporcionando tracción, conducción silenciosa y un manejo consistente para una conducción cómoda y agradable cada vez. El RIDGETRAK H/T HT02 está disponible de métrica de P y LT, con una garantía de millaje de 60,000 millas.

TRACCIÓN EXCELENTE

El compuesto de polímero especial con diseño de microsurcos en zig-zag mejora la tracción húmeda con control confiable para todo tipo de clima y de condiciones de camino.

COMODIDAD DE VIAJE

La tecnología de simulación de ruido moderna optimiza el diseño de la banda de rodamiento para una conducción silenciosa.

MANEJO UNIFORME

El diseño de barra de acoplamiento en los surcos laterales del hombro incrementa la estabilidad y promueve el desgaste regular.



RIDGETRAK H/T HT02

HIGHWAY TERRAIN / TERRENO DE CARRETERA


Part #	Size	P.R.	L/SR	TD	OD	SW	RW	UTQG	MAX LOAD (1X)	MAX LOAD (2X)
					32/in.	in.	in.		in.	lbs@psi
4120328V	235/75R15		105T	11	28.9	9.3	6.5	700 A A	2039@44	
4120323V	235/70R16		106T	11	29.0	9.4	7.0	700 A A	2094@44	
4120325V	245/70R16		107T	11	29.5	9.8	7.0	700 A A	2149@44	
4120322V	245/75R16		111T	11	30.5	9.8	7.0	700 A A	2403@44	
4120330V	255/70R16		111T	11	30.1	10.2	7.5	700 A A	2403@44	
4120317V	265/70R16		112T	11	30.6	10.7	8.0	700 A A	2469@44	
4120324V	265/75R16		116T	11	31.7	10.5	7.5	700 A A	2756@44	
4120326V	235/75R17		109T	11	30.9	9.3	6.5	700 A A	2271@44	
4120327V	245/65R17		107T	11	29.5	9.8	7.0	700 A A	2149@44	
4120318V	245/70R17		110T	11	30.6	9.8	7.0	700 A A	2337@44	
4120320V	265/65R17		112S	11	30.6	10.7	8.0	700 A A	2469@44	
4120301V	265/70R17		115T	11	31.7	10.7	8.0	700 A A	2679@44	
4120306V	255/70R18		113T	11	32.1	10.2	7.5	700 A A	2535@44	
4120307V	265/60R18		110H	11	30.5	10.7	8.0	700 A A	2337@44	
4120313V	265/65R18		114T	11	31.5	10.7	8.0	700 A A	2601@44	
4120311V	265/70R18		116T	11	32.6	10.7	8.0	700 A A	2756@44	
4120304V	275/65R18		116T	11	32.1	11.0	8.0	700 A A	2756@44	
4120310V	265/50R20		107V	11	30.5	10.9	8.5	700 A A	2149@44	
4120302V	275/55R20		117T XL	11	31.9	11.2	8.5	700 A A	2833@50	
4120303V	275/60R20		115T	11	33.0	11.0	8.0	700 A A	2679@44	
4120319V	285/45R22		114H XL	11	32.1	11.2	9.5	700 A A	2601@50	
4120316V	LT215/85R16	10PR	115/112R	14	30.4	8.5	6.0		2680@80	2470@80
4120315V	LT225/75R16	10PR	115/112R	14	29.3	8.8	6.0		2680@80	2470@80
4120334V	LT235/85R16	10PR	120/116R	14	31.7	9.3	6.5		3042@80	2778@80
4120332V	LT245/75R16	10PR	120/116R	14	30.5	9.8	7.0		3042@80	2778@80
4120333V	LT265/75R16	10PR	123/120R	14	31.7	10.5	7.5		3415@80	3085@80
4120331V	LT235/80R17	10PR	120/117R	14	31.8	9.3	6.5		3085@80	2835@80
4120321V	LT245/70R17	10PR	119/116S	14	30.6	9.8	7.0		3000@80	2755@80
4120329V	LT245/75R17	10PR	121/118S	14	31.5	9.8	7.0		3195@80	2910@80
4120314V	LT265/70R17	10PR	123/120S	14	31.7	10.7	8.0		3415@80	3085@80
4120309V	LT265/70R18	10PR	124/121S	14	32.6	10.7	8.0		3525@80	3195@80
4120308V	LT275/65R18	10PR	123/120S	14	32.1	11.0	8.0		3415@80	3085@80
4120305V	LT275/70R18	10PR	125/122S	14	33.2	11.0	8.0		3640@80	3305@80
4120312V	LT275/65R20	10PR	126/123S	14	34.1	11.0	8.0		3750@80	3415@80

50,000 Mile Limited Treadwear Warranty -LT sizes
60,000 Mile Limited Treadwear Warranty - P-metric sizes

ROVELO RIDGETRAK A/T II

ALL TERRAIN TIRE

PERFORMANCE RATINGS:



S, T AND R SPEED RATINGS

UTQG 620 A A



The Ridgetrak A/T II is an updated all-terrain tire for pickup trucks and SUVs. Enhanced 3PMS certified traction, deep tread depth while incorporating a wide tread face provides superior performance for all on and off road driving conditions. Known for consistent reliability, the Ridgetrak A/T II is engineered to be your trusted all-terrain tire providing a quiet comfortable driving experience.

COMFORT: Finite Element Analysis simulation software optimizes pitch sequence to reduce resonance effects and aids in a quiet vehicle cabin.

ENHANCED TRACTION: 3PMS Certified, deep all-terrain tread lugs and altered shoulder tread blocks work together providing trusted traction on all terrains and in all seasons.

TREADWEAR: A Wide tread footprint with additional shoulder support promotes even pressure distribution and avoids irregular wear.

El Ridgetrak A/T II es un neumático todoterreno actualizado para camionetas pickup y SUV. Tracción certificada 3PMS y profundidad de la banda de rodadura mejoradas, y la incorporación de una superficie de la banda de rodadura amplia proporciona desempeño superior para todas las condiciones de conducción dentro y fuera del camino. Conocidos por su confiabilidad constante, el Ridgetrak A/T está diseñado para ser su neumático todoterreno de confianza, que proporciona una experiencia de conducción cómoda y silenciosa.

COMODIDAD: El software de simulación de elemento finito optimiza la secuencia de paso para reducir los efectos de resonancia y ayuda a tener una cabina de vehículo silenciosa.

TRACCIÓN MEJORADA: Los gajos profundos de la banda de rodadura todoterreno y los bloques de la banda de rodadura del hombro, con certificación 3PMS, trabajan en conjunto para proporcionar tracción confiable en todos los terrenos y en todas las temporadas.

DESGASTE DE LA BANDA DE RODAMIENTO: La huella amplia de la banda de rodadura con apoyo de hombro adicional promueve distribución de presión más uniforme y evita el desgaste irregular.



RIDGETRAK A/TII

ALL TERRAIN TIRE

Part #	Size	Ply	LI/SR	TD	OD	SW	RW	UTQG	MAX LOAD (1X)	MAX LOAD (2X)
					32/in.	in.	in.			
4120258V	235/75R15	XL	109S	13	28.9	9.25	6	620 A B	2271@50	-
4120259V	235/70R16	-	106S	13	29.0	9.45	7	620 A B	2094@44	-
4120260V	245/75R16	-	111S	13	30.5	9.76	7	620 A B	2403@44	-
4120261V	265/70R16	-	112T	13	30.6	10.71	8	620 A B	2469@44	-
4120508V	265/75R16	-	116S	13	31.7	10.51	7	620 A B	2756@44	-
4120509V	235/65R17	-	104S	13	29.1	9.45	7	620 A B	1984@44	-
4120510V	245/65R17	-	107S	13	29.5	9.76	7	620 A B	2149@44	-
4120511V	245/70R17	-	110T	13	30.6	9.76	7	620 A B	2337@44	-
4120512V	255/65R17	-	110T	13	30.1	10.24	7	620 A B	2337@44	-
4120513V	265/65R17	-	112S	13	30.6	10.71	8	620 A B	2469@44	-
4120514V	265/70R17	-	115S	13	31.7	10.71	8	620 A B	2679@44	-
4120515V	265/65R18	-	114T	13	31.5	10.71	8	620 A B	2601@44	-
4120516V	265/70R18	-	116T	13	32.6	10.71	8	620 A B	2756@44	-
4120517V	275/65R18	-	116T	13	32.1	10.98	8	620 A B	2756@44	-
4120518V	265/50R20	XL	111T	13	30.5	10.91	8	620 A B	2403@50	-
4120519V	275/60R20	-	115T	13	33.0	10.98	8	620 A B	2679@44	-
4120526V	285/45R22	XL	114H	13	32.1	11.22	9	620 A B	2601@49	-
4120533V	LT225/75R16	10PR	115/112S	16	29.3	8.78	6	-	2680@80	2470@80
4120534V	LT235/85R16	10PR	120/116S	16	31.7	9.25	6	-	3042@80	2778@80
4120535V	LT245/75R16	10PR	120/116S	16	30.5	9.76	7	-	3042@80	2778@80
4120536V	LT265/75R16	10PR	123/120S	16	31.7	10.51	7	-	3415@80	3085@80
4120537V	LT235/80R17	10PR	120/117R	16	31.8	9.25	6	-	3085@80	2835@80
4120538V	LT245/70R17	10PR	119/116S	16	30.6	9.76	7	-	3000@80	2755@80
4120539V	LT245/75R17	10PR	121/118S	16	31.5	9.76	7	-	3195@80	2910@80
4120540V	LT265/70R17	10PR	121/118S	16	31.7	10.71	8	-	3415@80	3085@80
4120541V	LT285/70R17	10PR	121/118S	16	32.8	11.50	8	-	3750@80	3415@80
TBD	LT315/70R17	10PR	121/118S	16	34.4	12.72	9	-	3750@80	3415@80
4120543V	LT265/70R18	10PR	124/121S	16	32.6	10.71	8	-	3525@80	3195@80
4120544V	LT275/65R18	10PR	123/120R	16	32.1	10.98	8	-	3415@80	3085@80
4120545V	LT275/70R18	10PR	125/122R	16	33.2	10.98	8	-	3640@80	3305@80
4120546V	LT265/60R20	10PR	121/118R	16	32.5	10.71	8	-	3195@80	2910@80
4120547V	LT275/55R20	10PR	120/117R	16	31.9	11.18	8	-	3085@80	2835@80
4120548V	LT275/60R20	10PR	123/120R	16	33.0	10.98	8	-	3415@80	3085@80
4120549V	LT275/65R20	10PR	126/123R	16	34.1	10.98	8	-	3750@80	3415@80
4120550V	LT285/60R20	10PR	125/122R	16	33.5	11.50	8	-	3640@80	3305@80
4120551V	LT305/55R20	10PR	121/118R	16	33.2	12.44	9	-	3195@65	2910@65
4120527V	31x10.50R15LT	6PR	109S	16	30.5	10.55	8	-	2270@50	-
TBD	35x12.50R17LT	10PR	125R	16	34.2	12.5	10	-	3640@80	-
4120529V	33x12.50R18LT	10PR	118S	16	32.5	12.52	10	-	2910@65	-
4120531V	33x12.50R20LT	10PR	114S	16	32.5	12.52	10	-	2600@65	-
4120530V	35x12.50R18LT	10PR	123R	16	34.5	12.52	10	-	3415@65	-
4120532V	35x12.50R20LT	10PR	121R	16	34.5	12.52	10	-	3195@65	-


ROVELO

RIDGETRAK R/T



RUGGED TERRAIN LIGHT TRUCK

PERFORMANCE RATINGS:



S, T AND Q SPEED RATINGS
UTQG 600 A A



Meet the Ridgetrak RT tire, expertly engineered for trucks and SUVs. Its purpose-driven design features an optimized tread pattern that guarantees stability across various terrains. A sturdy sidewall with enhanced sidewall biters increases durability and adds to its striking appearance. With its robust visual appeal, this tire commands attention. The RIDGETRAK RT provides ample bite for off-road terrain while maintaining excellent road manners for your daily drive.

RIDE COMFORT

Staggered lateral grooves reduce road noise for the daily commute. While, interlocking tread blocks increase rigidity and eliminates road squirm on the deep RT treads.

DESIGNED WITH PURPOSE

Step-design shoulder lugs look aggressive and provide extra protection to the shoulders and sidewalls.

OFF-ROAD CAPABLE

Aggressive sidewall biters, scalloped alternating shoulders, and stone ejectors guarantee reliable traction.

Conozca al neumático Ridgetrak RT, diseñado con experiencia para camionetas y SUV. Su diseño orientado al propósito cuenta con un patrón de banda de rodamiento optimizado que garantiza la estabilidad en varios tipos de terreno. Una pared lateral robusta con hendiduras de pared lateral incrementa la durabilidad y suma a su apariencia impresionante. Con su robusto atractivo visual, este neumático atrae la atención. El RIDGETRAK RT proporciona un agarre amplio para terreno fuera del camino mientras mantiene excelentes modales para su conducción diaria.

COMODIDAD DE CONDUCCIÓN

Los surcos laterales escalonados reducen el ruido del camino del transporte diario. Entretanto, los bloques de la banda de rodamiento entrelazados incrementan la rigidez y eliminan el retorcimiento del camino en las bandas de rodamiento RT profundas.

DISEÑO CON PROPÓSITO

El diseño de los peldaños de gajos de hombro tienen una apariencia agresiva y proporcionan protección adicional a los hombros y a las paredes laterales.

CAPACIDAD PARA VIAJAR FUERA DEL CAMINO

Las agresivas hendiduras de la pared lateral, los hombros alternantes festoneados y los expulsores de piedras garantizan una tracción confiable.



RIDGETRAK R/T

RUGGED TERRAIN LIGHT TRUCK

Part #	Size	Ply	LI/SR	TD	OD	SW	RW	UTQG	MAX LOAD (1X)MAX LOAD (2X)		Stud Size
					32/in.	in.	in.		in.	lbs@psi	
1600404K	265/70R17	SL	115T	16	31.65	10.71	8	600 A B	2679@44	-	
1600420K	255/70R18	XL	116T	16	32.09	10.24	7	600 A B	2756@50	-	
1600403K	265/60R18	XL	114S	16	30.51	10.71	8	600 A B	2601@50	-	
1600415K	265/65R18	XL	116T	16	31.54	10.71	8	600 A B	2756@50	-	
1600417K	265/70R18	SL	116S	16	32.64	10.71	8	600 A B	2756@44	-	
1600407K	275/65R18	XL	116T	16	32.09	10.98	8	600 A B	2756@50	-	
1600433K	265/50R20	XL	111T	16	30.47	10.91	8	600 A B	2403@50	-	
5042036K	275/55R20	XL	117T	16	31.89	11.18	8	600 A B	2833@50	-	
1600421K	275/60R20	XL	116T	16	32.99	10.98	8	600 A B	2756@50	-	
1600422K	285/45R22	XL	114Q	16	32.09	11.22	9	600 A B	2601@50	-	
1600435K	LT245/70R17	10PR	119/116Q	18	30.55	9.76	7		3000@80	2755@80	15
1600430K	LT245/75R17	10PR	121/118Q	18	31.5	9.76	7		3195@80	2910@80	15
1600405K	LT265/70R17	10PR	123/120Q	18	31.65	10.71	8		3415@80	3085@80	15
1600412K	LT285/70R17	10PR	126/123Q	18	32.76	11.5	8		3750@80	3415@80	15
1600411K	LT265/65R18	10PR	122/119Q	18	31.54	10.71	8		3305@80	3000@80	15
1600429K	LT265/70R18	10PR	124/121Q	18	32.64	10.71	8		3525@80	3195@80	15
1600408K	LT275/65R18	10PR	123/120Q	18	32.09	10.98	8		3415@80	3085@80	15
1600432K	LT275/70R18	10PR	125/122Q	18	33.19	10.98	8		3640@80	3305@80	15
1600436K	LT275/55R20	10PR	120/117Q	18	31.89	11.18	8		3085@80	2835@80	15
1600434K	LT275/60R20	10PR	123/120Q	18	32.99	10.98	8		3415@80	3085@80	15
1600431K	LT275/65R20	10PR	126/123Q	18	34.09	10.98	8		3750@80	3415@80	15
1600428K	LT305/55R20	12PR	125/122Q	18	33.23	12.44	9		3640@80	3305@80	15
1600418K	33X12.50R17LT	10PR	120Q	18	32.52	12.52	10		3085@65	-	15
1600427K	35X12.50R17LT	10PR	125Q	18	34.53	12.52	10		3640@65	-	15
1600409K	37X12.50R17LT	8PR	124Q	18	36.54	12.52	10		3525@50	-	15
1600419K	33X12.50R18LT	12PR	122Q	18	32.52	12.52	10		3305@80	-	15
1600423K	35X12.50R18LT	12PR	128Q	18	34.53	12.52	10		3970@80	-	15
1600410K	37X12.50R18LT	10PR	128Q	18	36.54	12.52	10		3970@65	-	15
1600425K	33X12.50R20LT	12PR	119Q	18	32.52	12.52	10		3000@80	-	15
1600406K	35X12.50R20LT	12PR	125Q	18	34.53	12.52	10		3640@80	-	15
1600424K	35X13.50R20LT	12PR	126Q	18	34.53	13.58	10		3750@80	-	15
1600402K	37X12.50R20LT	10PR	126Q	18	36.54	12.52	10		3750@65	-	15
1600426K	33X12.50R22LT	12PR	114Q	18	32.52	12.52	10		2600@80	-	15
1600413K	35X12.50R22LT	12PR	121Q	18	34.53	12.52	10		3195@80	-	15
1600416K	37X12.50R22LT	12PR	127Q	18	36.54	12.52	10		3860@80	-	15
1600414K	37X13.50R22LT	12PR	128Q	18	36.54	13.58	10		3970@80	-	15

* LT tires are pinned for studs

ROVELO USA LIMITED WARRANTY

All Rovelo Tire warranties must be submitted through the point of purchase.

PASSENGER & LIGHT TRUCK TIRES

This Limited Warranty / Adjustment Policy provides for tire replacement under specified conditions. This policy applies to Rovelo tires used in normal highway service (commercial applications excluded) displaying warrantable conditions. Tires that become unserviceable or wear out because of neglect or mistreatment are excluded from Rovelo warranty coverage.

WARRANTY ELIGIBILITY

This warranty applies to every Rovelo replacement passenger car or light truck tire bearing the Rovelo brand name and complete Department of Transportation serial identification number while operated in normal highway use (commercial applications excluded) in the USA. These tires are covered by this warranty for the life of the original usable tread depth (the original tread depth down to the level of tread wear indicators molded at 2/32 inch) within 60 months from the date of purchase (proof of purchases required), or if proof of purchase is not available, the coverage will be 60 months from the date of manufacture. This warranty applies only to the original tire purchaser, and is not transferrable to any other party. This time period does not represent the expected service life for tires covered by this warranty.

WHAT IS NOT COVERED UNDER THIS LIMITED WARRANTY

- Improper repairs or repairs that have failed. Improper repairs will void this Limited Warranty.
- Improper maintenance which can include: improper inflation or other maintenance abuses
- Improper application or operations such as speeding, improper tire size and / or specification.
- Improper mounting / dismounting procedures, tire/wheel assembly imbalance.
- Mechanical irregularities in the vehicle or wheel, such as bent wheel assemblies, misalignment, worn or faulty components.
- Weather checking/cracking or failures after four years (48 months) from the date of manufacture.
- Accident, corrosion, vandalism, fire or damages caused by contamination by petroleum or other chemical products.
- Tires used in commercial applications such as taxis, shuttle vehicles and couriers.
- Irregular tread wear, or worn-out (beyond 2/32nds remaining tread depth) is not covered under the Rovelo Limited Warranty
- Road hazard injuries or damages caused by obstacles or debris, such as cuts, punctures (whether repairable or not), snags, bruises, tears, abrasions or impact breaks (whether repairable or not), etc.
- Damage from racing, off road use (forestry roads, gravel, rock) and misapplication of the tire to vehicle.

ADDITIONAL EXCLUSIONS

- Materials added such as fillers, sealants, balancing substances and external tire treatments. If the added material is the cause of a failure the warranty will be deemed as void.
- Tires submitted for ride disturbance complaints after 25% (2/32") tread wear.
- Tires on vehicles registered or operated outside of the USA.
- Tires not purchased in the USA through the Sailun Tire Americas distribution channel.
- Tires purchased as used.
- Tires branded by Rovelo to note special classification at time of purchase, such as "NA" (non-adjustable), or tires altered by notching or buffing.
- Tires used on vehicles in racing or special applications.
- Tires rendered unserviceable due to snow chains or studs.
- Flat spotting due to improper storage or caused by brake lock.

* Note: Consequential damage mentioned above may not apply to you based on individual State limitations.

WHAT IS WARRANTED

Tires that have become unserviceable for reasons other than stated above, within 48 months of the date of manufacturer or 60 months from the date of purchase (proof of purchase required) during its useable tread life, the tires will be replaced in accordance with this warranty.

ROVELO WARRANTY TABLE:

Model	Defects/ Materials	# Months	Miles/ Months
INSTINCT AS01	✓	60	60K/60
INSTINCT SUV	✓	60	60K/60
RIDGETRAK HT02 - LT Tires	✓	60	50K/60
RIDGETRAK HT02 - P- Metric Tires	✓	60	60K/60
RIDGETRAK A/T II	✓	60	50K/60*
RIDGETRAK R/T RT01	✓	60	45K/60*

Note: All tire models, staggered vehicle fitments have mileage for rear tires if different size than the front tires

Select Rovelo tires are assigned a Limited Mileage Warranty that protects the consumer against premature tread wear. If a tire reaches the end of its "usable tread life" before the stated mileage protection, the consumer will be issued a replacement Rovelo tire on a prorated basis, which means the consumer will be responsible for a percentage of the replacement cost. In order to maintain limited mileage protection, all tires must be properly inflated, balanced, rotated and aligned as recommended by vehicle manufacturer. All claims must be accompanied by the original purchase invoice as well as invoices for all on time services provided. Under all circumstances, the cost of mounting, balancing and any other service charges including applicable taxes, disposal fees are required to be paid by the consumer.

APPROVED TIRE ROTATION INTERVALS AND PATTERNS

The purpose of regularly rotating tires is to prolong their useful life by achieving more uniform wear for all tires on a vehicle. Before rotating tires, always consult the owner's manual for rotation recommendations for specific vehicles. If no rotation period is specified, tires should be rotated, at minimum, every 6,000 miles or at any sign of uneven wear. The first rotation is the most important. Rotating the tires as recommended by the vehicle or tire manufacturer will help even out the amount of wear on each tire and extend the life of the entire set. Such tires include: "Temporary Use Spares", unidirectional tires and tires with asymmetric tread designs. Also, some vehicles may have different sized tires mounted on the front and rear axles, and these different sized tires have rotation restrictions. Check the owner's manual for the proper rotation recommendations for these special cases. When tires are rotated, the inflation pressures must be adjusted for the tires' new positions in accordance with the actual loads on that wheel position and the vehicle manufacturer's recommendations. Underinflated or overinflated tires may result in poor handling, uneven tread wear, and increased fuel consumption. If the tires show uneven wear, ask the service person to check for and correct any misalignment, imbalance, or other mechanical problem before rotation.

ADJUSTMENT POLICY

Passenger and Light Truck Tires When the original usable tread is worn 25% (2/32 or less, and a warrantable condition is found, the tire will be replaced with a comparable new Rovelo tire free of charge. Replacement tires will be mounted and balanced at the vehicle owner's expense. Other service charges such as tire rotation, alignment or applicable taxes are payable by the customer. When a tire has worn past the above specified period for free replacement and a warrantable condition is found, the customer must pay for the cost of a new comparable Rovelo passenger or light truck tire on a prorated basis. The dealer shall determine this cost by multiplying the percentage of usable tread worn by the current retail selling price (Suggested Retail Price x 80%) of that tire at the time of warranty replacement. The cost of mounting, balancing and any other service charges or applicable taxes are





ROVELO

ROVELOTIREUSA.COM



Head office: 300 - 1 Kenview Blvd , Brampton, ON, L6T 5E6

Tel: (289) 499-3240 / Toll Free: 1-855-499-3240

V3.24U