



INSTINCT AW

ALL-WEATHER TIRE

Designed for year-round confidence, Rovel Instinct AW combines the agility of a high-performance all-season with the traction of a winter tire. Its asymmetric tread pattern offers superior grip and handling on wet, snowy, and dry roads, while the advanced rubber compound stays flexible even in sub-zero temperatures. With 3-Peak Mountain Snowflake (3PMSF) certification, it's ready for winter while delivering a quiet, comfortable ride in every season.

YEAR-ROUND CONVENIENCE

No seasonal tire change required, offering a cost-effective solution. Designed to handle both warm and cold conditions, with 3-Peak Mountain Snowflake certification.

CONSISTENT PERFORMANCE

The asymmetrical tread works in three zones: inner tread for water evacuation, outer tread for cornering and dry grip, and a center rib for stability and quick steering.

Diseñado para todo el año, Rovel Instinct AW combina la agilidad de un neumático de alto rendimiento con la tracción de invierno. Su dibujo asimétrico brinda agarre y control en mojado, nieve y seco, mientras que el compuesto avanzado permanece flexible en frío extremo. Con certificación 3PMSF, ofrece un viaje silencioso y cómodo en cualquier estación.

COMODIDAD TODO EL AÑO

No requiere cambio de neumáticos según la temporada, lo que ofrece una solución rentable. Diseñado para soportar condiciones tanto cálidas como frías, con certificación 3-Peak Mountain Snowflake.

RENDIMIENTO CONSTANTE

La banda de rodadura asimétrica funciona en tres zonas: banda de rodadura interior para la evacuación del agua, banda de rodadura exterior para tomar curvas y tener agarre en seco, y una nervadura central para estabilidad y dirección rápida.





Size	Service Desc.	L.R.	TD	OD	SW	RW	UTQG	MAX LOAD (1X)
			32/in.	in.	in.	in.		lbs@psi
185/65R15	88H		11	24.4	7.4	5.5	500 A A	1235@44
195/65R15	91H		11	25.0	7.9	6.0	500 A A	1356@44
205/55R16	91V		11	24.9	8.4	6.5	500 A A	1356@44
205/60R16	96V	XL	11	25.7	8.2	6.0	500 A A	1565@50
205/65R16	95H		11	26.5	8.2	6.0	500 A A	1521@44
215/55R16	93V		11	25.3	8.9	7.0	500 A A	1433@44
215/60R16	99H	XL	11	26.1	8.7	6.5	500 A A	1709@50
215/65R16	102H	XL	11	27.0	8.7	6.5	500 A A	1874@50
235/70R16	106H		11	29.0	9.4	7.0	500 A A	2094@44
205/50R17	93V	XL	11	25.1	8.4	6.5	500 A A	1433@50
215/45R17	91W	XL	11	24.6	8.4	7.0	500 A A	1356@50
215/50R17	95W	XL	11	25.5	8.9	7.0	500 A A	1521@50
215/55R17	98V	XL	11	26.3	8.9	7.0	500 A A	1653@50
215/60R17	100H	XL	11	27.2	8.7	6.5	500 A A	1764@50
215/65R17	103H	XL	11	28.0	8.7	6.5	500 A A	1929@50
225/45R17	94V	XL	11	25.0	8.9	7.5	500 A A	1477@50
225/50R17	98V	XL	11	25.9	9.2	7.0	500 A A	1653@50
225/55R17	101V	XL	11	26.8	9.2	7.0	500 A A	1819@50
225/60R17	103H	XL	11	27.6	9.0	6.5	500 A A	1929@50
225/65R17	102H		11	28.5	9.0	6.5	500 A A	1874@44
235/55R17	103V	XL	11	27.2	9.6	7.5	500 A A	1929@50
235/65R17	108H	XL	11	29.1	9.4	7.0	500 A A	2205@50
225/40R18	92V	XL	11	25.1	9.1	8.0	500 A A	1389@50
225/45R18	95V	XL	11	25.9	8.9	7.5	500 A A	1521@50
225/50R18	99V	XL	11	26.9	9.2	7.0	500 A A	1709@50
225/55R18	102V	XL	11	27.8	9.2	7.0	500 A A	1874@50
225/60R18	104H	XL	11	28.6	9.0	6.5	500 A A	1984@50
235/40R18	95V	XL	11	25.4	9.5	8.5	500 A A	1521@50
235/45R18	98W	XL	11	26.3	9.3	8.0	500 A A	1653@50
235/50R18	101V	XL	11	27.3	9.6	7.5	500 A A	1819@50
235/55R18	104V	XL	11	28.1	9.6	7.5	500 A A	1984@50
235/60R18	107H	XL	11	29.1	9.4	7.0	500 A A	2149@50
235/65R18	110H	XL	11	30.0	9.4	7.0	500 A A	2337@50
245/40R18	97W	XL	11	25.7	9.8	8.5	500 A A	1609@50
245/60R18	109H	XL	11	29.6	9.8	7.0	500 A A	2271@50
225/55R19	103V	XL	11	28.8	9.2	7.0	500 A A	1929@50
235/40R19	96V	XL	11	26.4	9.5	8.5	500 A A	1565@50
235/50R19	103W	XL	11	28.3	9.6	7.5	500 A A	1929@50
235/55R19	105V	XL	11	29.2	9.6	7.5	500 A A	2039@50
245/45R19	102V	XL	11	27.7	9.6	8.0	500 A A	1874@50
255/35R19	96V	XL	11	26.0	10.2	9.0	500 A A	1565@50
255/40R19	100V	XL	11	27.0	10.2	9.0	500 A A	1764@50
235/55R20	105V	XL	11	30.2	9.6	7.5	500 A A	2039@50
245/45R20	103V	XL	11	28.7	9.6	8.0	500 A A	1929@50
245/50R20	105V	XL	11	29.7	10.0	7.5	500 A A	2039@50
255/45R20	105V	XL	11	29.1	10.0	8.5	500 A A	2039@50
265/50R20	111V	XL	11	30.5	10.9	8.5	500 A A	2403@50
235/65R16C	121/119R	E	13	28.0	9.4	7.0		3197@83